



Industrial Hydraulic Services Pty Ltd

ABN 40 004 985 559

371-397 Plummer Street, Port Melbourne, Victoria, Australia, 3207

Tel: +61 3 9645 1522 Fax: +61 3 9646 5966

Email: info@ihs-aust.com.au Web: www.ihs-aust.com.au

ISEKI



FOR FURTHER INFORMATION, PRICING, SALES & SERVICE CONTACT:

HILTON FORD - MACHINERY SALES

PH: 0448 309 365 FAX: 03 9646 5966 EMAIL: hilton@ihs-aust.com.au



MASSEY FERGUSON



ISEKI SZ MOWER



33hp

SZ Zero-Turn Mower

Smart, Reliable...
Created with you in mind.



SMART, RELIABLE,
CREATED WITH YOU IN MIND

ISEKI

ISEKI SZ ZERO-TURN MOWERS

The new SZ Zero-Turn mower continues Iseki's tradition of delivering equipment that is reliable, hard-working and offers the most advanced engineering.

It all begins with you - your efficiency, comfort and ability to add value to the bottom line. With the Iseki SZ you can rest easy knowing that you have a diesel engine packing 33hp with the largest radiator on the market in its class. Your Iseki SZ will provide the stability and power needed to handle the toughest of jobs, day in, day out.

Designed and built for the professional operator, the Iseki SZ provides the smooth ride required for those days when many hours are spent behind the wheel. Sensibly laid out controls located within arms-reach add to the driving experience. And with lower operating costs and superior fuel efficiency, the Iseki SZ becomes the perfect partner for your operations.

THE ISEKI DIFFERENCE

When you choose Iseki, you're not simply buying a tractor, you're investing in 80 years of industry-leading engineering and manufacturing experience. Experience that continues to produce high quality and top performing products that are built to meet today's ever increasing demands.

While Iseki has made its mark internationally, you can still feel confident knowing that they understand the unique industries of each country. During their 25 years in the Australian market they have built solid and reliable foundations, continuously delivering superb products and services that work even harder for your specific needs.

You get the expertise of your local Iseki dealer who will match the right tractor to your business and even provide flexible finance options to help fund your purchase.

Combine this with peace of mind from first-class parts and service support and you'll see what we mean by the Iseki Difference.

FEATURES



MOWER DECK

- Deep deck design to handle large volumes of grass.
- Three blade side discharge deck with large 1.83m (72") cutting width.
- Robust one piece pressed steel construction.
- Anti-scalloping rollers and gauge wheels for an even cutting height.



DECK LIFT / JACK

- Convenient crank lift mechanism allows the front of the mower to be easily raised.
- Regular maintenance, inspection and replacement of blades made easy.
- Quick and easy to activate, with no heavy lifting required.
- 45 degree flip-up.



CUTTING HEIGHT ADJUSTMENT

- Cutting height is quickly and easily adjusted by the turn of a dial.
- Numeric setting is clearly visible for accurate calibration.
- Adjustment range from 25mm to 115mm.
- Controls are easily accessed from the operator's seat and can be adjusted on-the-move.

Zero-Turn Diesel Mower **33hp**



FOLDING ROPS FRAME

- Foldable ROPS as standard.
- Allows the mower to pass under low overhead obstacles.
- Quick and simple to activate - simply remove 2 pins and fold.



SERVICE AND MAINTENANCE

- Full opening hood and folding seat for easy service and maintenance.
- Allows for quick access to all mechanical and operational parts.
- Filling points and filters are easily accessible.



CONTROL PANEL

- Conveniently grouped controls for ease of use and operation on-the-move.
- Independent electro hydraulic PTO engagement.
- Monitoring indicators for temperature (with warning buzzer), oil pressure and battery charge.
- Throttle lever, fuel gauge and hour meters.

ISEKI SZ SPECIFICATIONS

SZ ZERO TURN MOWER

ENGINE

Model	Iseki EC3D-G01 Diesel
Number of cylinders	3
Displacement	1498cc
Output	33hp@2600 rpm

POWER TRAIN

Transmission type	Hydrostatic
Ranges	1
Speeds	Forward: 0 – 17 km/h Reverse: 0 – 8 km/h
Drive	2WD

MID PTO

Speed	2100 rpm
Clutch	Multi wet disc

STEERING

Type	Two hand levers
------	-----------------

BRAKES

Type	Dry internal shoe
------	-------------------

TYRE SIZE

Front	15 x 6.0 – 6
Rear	26 x 12.0 – 12

DIMENSIONS

Overall length	2320 mm
Overall width	1480 mm
Overall height folded	1290 mm
Overall height top	1950 mm
Wheel base	1450 mm
Ground clearance	120 mm
Weight	620 kg
Turning circle	0.0 mt

MOWER DECK

Model	SSM72
Type	Rotary mower
Cutting width	1830 mm
No. of blades	3
Drive	Shaft
Rotor drive	Double belt
Deck lifting	Hydraulic
Cutting height	25 – 115 mm by dial
Scallop rollers	Standard
Discharge	Side
Deck service	45° crank up deck

MOWER DECK DIMENSIONS

Overall width	2280 mm
Overall height	521 mm
Overall length	1165 mm
Weight	210 kg



Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.

www.agco.com.au



smart, reliable created with you in mind



FREECALL: 1800 802 914